

AVL

For Peak Performance

THICK

- Long Lasting Rust Protection and Lubrication
- Penetrates Fast to Displace Moisture
- Contains No CFCs or Chlorinated Solvents
- Sprays Upright or Inverted

Part No. AVL-HW16

DANGER: CONTENTS UNDER PRESSURE. HARMFUL OR FATAL IF SWALLOWED.

READ CAUTIONS ON BACK LABEL.

NET WT. 11 OZ. (312 g)

AVL

THICK

The premium thick lubricant and corrosion preventor. Penetrates and displaces moisture. It stops corrosion on contact leaving a thick coating for long term lubrication and corrosion prevention. Can sprays upright or inverted.

Directions: Shake well and apply to clean surface. If necessary repeat application. Remove with AVL degreasing products. Use attached extension tube for spraying hard to reach areas.

For general purpose lubrication and corrosion prevention with an oily film use AVL MEDIUM. For a lighter coating of rust protection and lubrication on fine machinery use AVL LIGHT.

Applications

Airframe Interiors	Outdoor Equipment
Aircraft Fuselages	Hinges and Locks
Bare Metals	Frozen Parts
Chains and Cables	Antennaes
Battery Terminals	Parts Exposed to Salts
Boat Trailers	Trucks and Tractors
Doors and Fasteners	Outdoor Tools

Environmentally Friendly

- Contains No CFCs
- Workplace Safe
- Non-Conductive
- Non-Flammable Propellant

AVL THICK has been formulated to displace moisture, lubricate, and protect against rust. It penetrates, displaces moisture and stops rust quickly, to provide a long lasting thick film.

DANGER: COMBUSTIBLE. KEEP AWAY FROM CHILDREN: Contains petroleum distillates do not puncture, incinerate or store can above 120F. Keep away from exposed flame or sparks. Do not store near sources of heat or direct sunlight. Exposure to high temperatures may cause can to burst. Avoid contact with skin and eyes and breathing of vapors. Use with proper ventilation. **HARMFUL OR FATAL IF SWALLOWED. DO NOT INDUCE VOMITING. IF SWALLOWED CALL PHYSICIAN IMMEDIATELY.** Use only as directed. In case of eye or skin contact flush with water for 15 minutes. Deliberate misuse by concentrating or inhaling the contents can be harmful or fatal.

Right to know: Aliphatic Hydrocarbon 6472-88-7, Carbon Dioxide Propellant 124-38-9.

A product of Aviation Laboratories, Houston, TX 77092

Telephone Toll Free 1-800-256-6876

Emergency Phone CHEMTREC 1-800-424-9300

Visit our Web Site at www.AVLAB.com

1993 AVL is a trademark of Aviation Laboratories Inc.