

AVL

For Peak Performance

## **MEDIUM**

- Penetrates and Helps Free Corroded Parts
- Penetrates Fast and Displaces Moisture
- Coats Surfaces For Up To One Year
- Oily Coating Won't Dry Out
- Contains No CFCs or Chlorinated Solvents
- Sprays Upright or Inverted

Part No. AVL-MW16

DANGER: CONTENTS UNDER PRESSURE. HARMFUL OR FATAL IF SWALLOWED.  
READ CAUTIONS ON BACK LABEL.

NET WT. 11 OZ (312 g)

AVL

## **MEDIUM**

**The premium Medium lubricant and corrosion preventor. It is specifically designed for penetrate and displace moisture fast. It leaves a medium weight oily coating for long term lubrication and rust prevention. Can spray upright or inverted.**

**Directions:** Shake well and apply to clear surface. If necessary repeat application. Remove with AVL degreasing products. Use attached extension tube for spraying hard to reach areas. For thick lubrication and corrosion prevention use AVL THICK. For a lighter coating of rust protection lubrication on fine machinery use AVL LIGHT.

### **Applications:**

Pulleys and Shafts	Outdoor Equipment
Pumps and Clamps	Hinges and Locks
Bare Metals	Frozen Parts
Chains and Cables	Antennas
Drill Bits	Hand Tools
Electric Motors	Nuts and Bolts
Doors and Fasteners	Outdoor Tools

## **Environmentally Friendly**

Contains No CFCs

Workplace Safe

Non-Conductive

Non-Flammable Propellant

**AVL Medium** has been formulated to displace moisture, lubricate, and protect against rust. It penetrates, displaces moisture and stops rust quickly, to provide a long lasting medium weight oily film.

**DANGER: COMBUSTIBLE. KEEP AWAY FROM CHILDREN:** Contains petroleum distillates do not puncture, incinerate or store can above 120F. Keep away from exposed flame or sparks. Do not store near sources of heat or direct sunlight. Exposure to high temperatures may cause can to burst. Avoid contact with skin and eyes and breathing of vapors. Use with proper ventilation. **HARMFUL OR FATAL IF SWALLOWED. DO NOT INDUCE VOMITING. IF SWALLOWED CALL PHYSICIAN IMMEDIATELY.** Use only as directed. In case of eye or skin contact flush with water for 15 minutes. Deliberate misuse by concentrating or inhaling the contents can be harmful or fatal.

Right to know: Aliphatic Hydrocarbon 6472-88-7, Petroleum Oil 6472-53-6, Petroleum Oil 6472-52-5, Carbon Dioxide Propellant 124-38-9.

A product of Aviation Laboratories, Houston, TX 77092

Telephone Toll Free 1-800-256-6876

Emergency Phone CHEMTREC 1-800-424-9300

Visit Our Web Site at [www.AVLAB.com](http://www.AVLAB.com)

1993 AVL is a trademark of Aviation Laboratories Inc.